

TK-II-PIGGYBACK

Bill of Materials

QTY	Part Number	Description
1	PIC16F1847	18 pin DIP Flash Microcontroller 16 I/O lines Internal 32 Mhz Oscillator 14 Kbytes Program Memory 1024 bytes Linear Data Memory 256 bytes Data EEPROM
1	526213	18 pin IC Socket
1	P20R104K5-F	0.1uf axial capacitor
1	233453	Molex Right Angle 4 Pin 0.1" PCB Connector
1	234819	Molex 4 Position 0.1" Housing
4	234931	Molex Connector Contact Female Crimp
1	203932	Right Angle 10 pin DIL 0.1" Un-Shrouded Header – See Note
2	PLATE6F	StarTech 6 pin MiniDin PS/2 Panel Connector – See Note
1	740-AG14D	AUGAT 40 pin DIP Break-Away Socket Carrier

With the exception of the microcontroller, and the last two items, all part numbers are for Jameco.com

Note: You can substitute the TK-II-INTFC board for the StarTech connectors, and a Jameco p/n 2167939 Shrouded Right-Angle Header for J1 on the TK-II-PB.

The [AUGAT 740-AG14D](#) was purchased as a surplus item from electronicsurplus.com



AUGAT - 740-AG14D - IC Socket. 40-pin break-away.

[Email to a Friend](#)

IC Socket. 40-pin break-away. Machined brass pins, gold-plated over nickel. 0.010" centers. Disposable aluminum carrier. 740-AG14D, Seagate# 10506-040.

Availability: **In stock**

\$1.50

Qty:

Add to Cart

[Add to Wishlist](#) [Add to Compare](#)